

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 April 2004 (15.04.2004)

PCT

(10) International Publication Number
WO 2004/032565 A2

- (51) International Patent Classification⁷: H04R
- (21) International Application Number: PCT/NL2003/000677
- (22) International Filing Date: 3 October 2003 (03.10.2003)
- (25) Filing Language: Dutch
- (26) Publication Language: English
- (30) Priority Data:
1021588 5 October 2002 (05.10.2002) NL
- (71) Applicant (*for all designated States except US*): AUDILUX N.V. [NL/NL]; Javastraat 102, NL-2585 AV Den Haag (NL).
- (72) Inventor; and
(75) Inventor/Applicant (*for US only*): BORDEWIJK, Lourens, George [NL/NL]; Javastraat 102, NL-2585 AV Den Haag (NL).
- (74) Agent: VAN WESTENBRUGGE, Andries; Nederlands Octrooibureau, Scheveningseweg 82, P.O. Box 29720, NL-2502 LS The Hague (NL).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— without international search report and to be republished upon receipt of that report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



WO 2004/032565 A2

(54) Title: HEARING AID WITH PULL CORD

(57) Abstract: Hearing aid comprising two parts that can be joined together/taken apart. One part is provided with the electronics and preferably consists of a universal part. The other part comprises an accommodation for the battery and is matched to the wearer's auditory canal. Both parts are provided with a pull cord for removing from the ear and separating the parts from one another. These pull cords are preferably in contact with one another.

Hearing aid with pull cord

The present invention relates to a hearing aid comprising two parts that can be joined together/taken apart, as well as a pull cord for removing said hearing aid from the auditory canal.

More particularly, the present invention relates to hearing aids that are fitted deep in the auditory canal. These hearing aids are also termed CIC (completely-in-the-canal) aids and are marketed under the trade name Microlux by Audilux N.V. in The Hague.

Hearing aids of this type consist of two parts. In a particular variant the first part is provided with the electronics and the second part is mainly an accommodation for a battery. Moreover, one of the parts is preferably of universal construction and the other part is matched to the auditory canal of the wearer.

Under all circumstances it must be possible to remove the hearing aid from the ear. Moreover, it must be possible to separate the two parts, for example to replace/charge the battery or to perform other activities. Separation of the two parts is also necessary for cleaning, for example the removal of earwax.

It is known to provide such a hearing aid with a single pull cord that is permanently attached. This protrudes from the auditory canal to only a slight extent and the wearer can remove the hearing aid by pulling. As indicated, under some circumstances it can be necessary to separate the two parts from one another after removal from the ear. A wide variety of methods are used for this purpose in the state of the art. Pushing a rod or the like through the second part, as a result of which the first part is detached from the second part, may be mentioned as an example. Other methods are also known, but these all have in common that uncontrolled, and possibly high, forces are applied to the parts, as a result of which damage regularly occurs.

The aim of the present invention is to avoid the disadvantages described above.

This aim is realised with a hearing aid as described above in that each of said parts is provided with a pull cord attached thereto.

According to the present invention each part is provided with a pull cord. By this means it is possible to separate the parts from one another after removing from the ear. Moreover, the presence of two pull cords provides the wearer with (psychological) assurance that should one of the cords break it is still easily possible to remove the aid from the ear.

According to an advantageous embodiment, the two parts can be fitted in only one position with respect to one another. In order to make the pull cords as invisible as possible to the outside world, in such an embodiment provision is made that the pull cords are arranged lying on top of one another. Apart from the fact that the pull cords are less visible, 5 this has the advantage that when grasped by the wearer the two pull cords are automatically pressed against one another and the pull force exerted by the wearer is distributed uniformly over the pull cords.

As described above, the first part preferably contains the electronics, comprising microphone, loudspeaker and the like. This part is preferably of universal construction.

10 The second part is preferably matched to the wearer's auditory canal. This can be achieved by providing one or more standard covers that are capable of being coupled to the first part. Such a coupling preferably comprises sliding into one another, the cover being on the outside. Preferably, that cover that is smaller than the user's auditory canal is chosen from these standard covers. Material is then applied to the cover by injection and/or 15 bonding techniques, as a result of which the appearance of the second part obtained in this way precisely corresponds to the shape of the wearer's auditory canal.

It will be understood that the method for obtaining the second part is not essential for the use of the two pull cords according to the present invention.

The pull cords are preferably so made that these are not conspicuous. That is to say, 20 they can have a colour that corresponds to the body colour or can be made transparent. The pull cord preferably consists of a very strong material, such as a nylon material. It can be provided with profiling to give better grip. It is also possible to make the pull cord integral with one of the parts.

According to a further advantageous embodiment, the hearing aid is not circular. 25 More particularly, there is a clear preferred position for fitting in the auditory canal. In such preferred position provision is made that the pull cords are arranged on the side of the wearer's face. That is to say, the pull cords are arranged in the shadow of the aid itself and of the tragus. The pull cords are least conspicuous in this position. In addition, the first part and the cover that forms the base for the second part can still be universal. Even if, for 30 example, the first part is curved to some extent in the direction of the longitudinal axis of the auditory canal, which is desirable in practice in order to provide an optimum fit, positioning on the face side will still be possible in the case of left/right fitting.

The invention will be explained in more detail below with reference to an illustrative

embodiment shown in the drawing. In the drawing:

Fig. 1 shows the various components from which the hearing aid according to the invention is constructed;

Fig. 2 shows the two parts of the hearing aid according to the invention before
5 joining together;

Fig. 3 shows the hearing aid when joined together; and

Fig. 4 shows the positioning of the pull cords according to the invention with respect to the ear.

In Fig. 3 the hearing aid according to the invention is indicated in its entirety by 1. As
10 can be seen from Figs. 1 and 2, this hearing aid consists of two parts, a first part 2 and a second part 3. The first part 2 is a preferably universal part and is provided with electronics. These are understood to be a microphone, amplifier and loudspeaker. Furthermore, there are terminals or the like, which are not shown in more detail, for accommodating a battery 10. There can also be on/off switches, controls, links to
15 programming computers and the like. For details reference is made to other patents/applications filed in the name of Audilux. Part 2 is made somewhat curved in the longitudinal direction thereof in order to provide an optimum match to the auditory canal. There is a keyhole-shaped channel 4 in the first part 2. This is made to accommodate a pull
20 cord 5, which is provided with thickenings 6. This pull cord 5 preferably consists of a transparent material of high strength, such as nylon material. One example is nylon 5 or 6. The end thickening of the pull cord 5 fits precisely in the widened part of the accommodation and the relevant parts can then be fixed by bonding.

The second part 3 comprises, as supplied by the manufacturer, a cover 11 with a pull
cord 7 attached integrally thereto.

25 Covers 11 of various sizes or customised covers 11 can be made available. Thickenings 8 are then made on these covers 11, as can be seen from Fig. 2. This can take place using bonding techniques or using injection techniques. One example therefor is described in PCT application PCT/NL/02/00100 in the name of Audilux.

The cover 11, or the second part 3, is so constructed that this can be pushed over the
30 first part 2 only in one position. This is shown in Fig. 3, from which it can be seen that the pull cords 5 and 7 are arranged in contact with one another.

The right ear of a wearer is shown diagrammatically in Fig. 4. When the hearing aid 1 according to the present invention is fitted in the ear, this hearing aid is invisible. Only the

pull cords 5 and 7 protrude. As can be seen from Fig. 4, these are on the face side, on the right in the "three o'clock position" and on the left in the "nine o'clock position". It is possible to achieve the same effect on the wearer's left side with the aid of the same universal part 2 and an adapted cover 11.

- 5 If the hearing aid has to be removed from the ear, the user presses the two pull cords 5 and 7 together using his or her fingers and then exerts force. During this operation the profiling 6 presses against the pull cord 7, as a result of which maximum grip and force distribution are provided. In this way the aid is removed from the ear with relatively little effort. If the user then wishes to separate parts 2 and 3 in order to change the battery, or for
10 cleaning purposes, or for other reasons, he or she simply holds part 3 firmly and pulls on cord 5 to remove part 2 that has been pushed into part 3.

- Although the invention has been described above with reference to a preferred embodiment, it will be understood by those skilled in the art that numerous modifications can be made which are immediately obvious and fall within the scope of the appended
15 claims.

CLAIMS

1. Hearing aid (1) comprising two parts (2, 3) that can be joined together/taken apart, as well as a pull cord for removing said hearing aid from the auditory canal, characterised in
5 that each of said parts (2, 3) is provided with a pull cord (5, 7) attached thereto.
2. Hearing aid according to Claim 1, wherein said parts are fitted only in one position with respect to one another and wherein said pull cords are arranged at least partially in contact with one another in said position.
- 10 3. Hearing aid according to one of the preceding claims, wherein said parts comprise a first universal part (2) provided with a microphone, electronics and loudspeaker.
4. Hearing aid according to one of the preceding claims, wherein said parts comprise a
15 second part (3) that has been matched to the user's auditory canal and is designed to accommodate a battery (10).
5. Hearing aid according to one of the preceding claims, wherein said parts can be slid into one another.
- 20 6. Hearing aid according to one of the preceding claims, wherein one pull cord is provided with profiling (6).
7. Hearing aid according to one of the preceding claims, wherein one pull cord is
25 essentially smooth.
8. Hearing aid according to one of the preceding claims, wherein one pull cord comprises a nylon material.
- 30 9. Hearing aid according to one of the preceding claims, wherein said pull cord (5) comprises a separate part provided with a thickened end (6), accommodated in a recess (4) in one of said parts.

10. Hearing aid according to one of the preceding claims, wherein said parts are of non-circular construction such that when fitted in the auditory canal said pull cord is on the face side of the auditory canal.

Fig 1




Fig 2




Fig 3





Fig 4



INTERNATIONAL SEARCH REPORT

International Application No.

PCT/NL 03/00677

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H04R25/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 H04R

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2001/043708 A1 (BRIMHALL OWEN D) 22 November 2001 (2001-11-22) abstract paragraph '6470!; figures 7,8	1-5,7

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- *G* document member of the same patent family

Date of the actual completion of the international search

27 May 2004

Date of mailing of the international search report

07/06/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3018

Authorized officer

Fuchs, P

INTERNATIONAL SEARCH REPORT

onal Application No
PC1/NL 03/00677

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 2001043708	A1	22-11-2001	AU	2225700 A	01-08-2000
			WO	0042817 A1	20-07-2000